



Logo Placements

2864 Sweatshirt, CI 3

Recommended logo placements

Heat seal & Embroidery

- 1 Left breast, 1 cm above pocket, maximum size 60x60 mm
- 2 Left sleeve, 5 cm below shoulder seam, maximum size 120x120 mm
- 3 Right breast, maximum size 90x60 mm, in line with placement 1
- 4 Right sleeve, 5 cm below shoulder seam, maximum size 120x120 mm
- 6 Back, 12 cm below neck seam, maximum size 220x180mm
- 23 Right breast, top of logo in line with top of zipper, maximum size 90x120mm
- 63 Back, 2 cm above end seam, maximum size 280x50mm

To maintain 3 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.



Maximum size of logo cm² to keep classification EN 20471

Size	cm ²	cm
All	1300	36x36



How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm² shall be tested in ISO 15025, Procedure A.



Add

B after the placement and it will be below the (1B)

Y and it will be turned from bottom to top

Z after the placement and it will be turned from top to bottom

