



# Logo Placements

## 6365 PW, Trousers, HV CI 1

### Recommended logo placements

#### Heat seal & Embroidery

18 Centered at right hip-pocket, maximum size 100x80mm

#### Heat seal

- 19 Right leg pocket, maximum size 100x40 mm
- 20 Left leg pocket, maximum size 100x40 mm
- 29 Right thigh-pocket flap, maximum size 120x30 mm
- 30 Left thigh-pocket flap, maximum size 100x30 mm



Maximum size of logo cm<sup>2</sup> to keep classification EN 20471

Size	cm <sup>2</sup>	cm
All sizes	3900	62x62

To maintain the Class 2 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.



How to keep classification ISO EN 11612

- 1Y** Add
- 1** B after the placement and it will be below the (1B)
- 1B** Y and it will be turned from bottom to top
- 1Z** Z after the placement and it will be turned from top to bottom

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm<sup>2</sup> shall be tested in ISO 15025, Procedure A.



Right side of trouser



Left side of trouser